

INCEPTOR® DUO



Technical Specification

Product Code: OXD442-G-MF

Luckinslive 436166262



Description: 36W Down & 6W Up, Suspended Linear, 2 in 1 Dimmable & Dual CCT Switchable
– Grey



General Information

Dimensions (mm)	1120 (L) x 40 (W) x 100 (D)
Materials	Housing & Ceiling Rose: Aluminium Diffusers: Polycarbonate
Colour	Grey (RAL7030)
Product Weight (Kg)	2.03
Ingress Protection	IP20
Mounting	Suspended
Fixing Components Supplied	Surface Brackets For Ceiling Roses
Warranty (Years)	5
On Site Warranty	1 Year Unregistered, 2 Year Registered (https://oviauk.com/on_site_warranty)

Supply & Power Information

Continuous Operating Voltage (AC) (Hz)	220-240 (50/60)
Safety Class	I
Circuit Wattage (W)	42
LED Wattage (W)	36 (Down) & 6 (Up)
Inrush Current	5A (170µs)
Power Factor	>0.9
Operating Temperature (°C)	-15 to +45
Maximum Critical Temperature (°C)	85
Input Terminations	4 + 2 Pole Push Fit Terminals

Luminaire Output

Colour Temperature (K)	3000	4000	6000
Upwards Typical Luminous Flux (lm)	300	330	300
Downwards Typical Luminous Flux (lm)	3800	4000	3800
Upwards Efficacy (lm/W)	50	55	50
Downwards Efficacy (lm/W)	105	111	105
Overall Efficacy (lm/W)	97	103	97
Beam Angle (°)	100		
Colour Rendering Index (CRI)	>80		
Flicker Free	Yes		
LED Lifetime (L70) (Hours)	50000		

Dimming Information

Dimmable	Yes
Dimming Format	DALI & Switch Dim

Additional Information

Up and Down each has switchable CCT and switch Off option.
Both Up and Down outputs dim together.



OVIA Limited, Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 300640
E: sales@oviaUK.com | W: oviaUK.com



Catalogue



Section



DoC



Installation

