


INCEPTOR® HI-LITE

Technical Specification

Product Code: OXHL200

Description: 200W LED 0(1)-10V Dimmable Highbay IP65 CCT

Luckinslive 434776188



General Information

Dimensions (mm)	336 (Dia.) x 102 (D)
Materials	Body: Powder Coated Aluminium; Diffuser: Polycarbonate
Colour	Black (RAL9005)
Product Weight (Kg)	3.1
Ingress Protection	IP65
Impact Rating (IK)	10
Fixing Components Supplied	Suspension Point Within Moulding
Warranty (Years)	6
On Site Warranty	1 Year Unregistered, 2 Year Registered (https://oviauk.com/on_site_warranty)

Supply & Power Information

Continuous Operating Voltage (AC) (Hz)	220-240 (50/60)
Safety Class	I
Circuit Wattage (W)	200
LED Wattage (W)	200
Input Current (mA)	722-1000
Inrush Current	75A (288µs)
Power Factor	>0.9
Operating Temperature (°C)	-40 to +50
Minimum Critical Temperature (°C)	-40
Maximum Critical Temperature (°C)	+90
Input Mains Cable	3 x 1mm ² H05RN-F (3 Metres)
Analogue Input Cable 0(1)-10V	2 x 20 AWG (3 Metres) - Black

Luminaire Output

Colour Temperature (K)	4000	5000	6500
Typical Luminous Flux (lm)	31000	33000	30000
Efficacy (lm/W)	155	165	150
Beam Angle (°)	90		
Colour Rendering Index (CRI)	80		
Flicker Free	Yes		
LED Lifetime (L70) (Hours)	50000		

Dimming Information

Dimmable	Yes
Dimming Format	0(1)-10V

Compatible Accessories

OVWB1082 - Black Bracket For 200W Inceptor® Hi-Lite Highbay Fitting
OXHLEP - 5W 3 Hour Maintained IP65 Emergency Pack
OEPCL05 - Highbay Emergency Pack Coupler Lead 0.5M
OEPCL1 - Highbay Emergency Pack Coupler Lead 1M
OVHBDACV - IP67 DALI To PWM Signal Converter

Additional Information

Shorting cap supplied which is removable for emergency pack installation



OVIA Limited, Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom

T: +44 (0)1827 300640

E: sales@oviaUK.com | W: oviaUK.com



CLICK OR SCAN

Catalogue



Section



DoC



Installation



CLICK OR SCAN