



Product Code: PRC210AG

Luckinslive 391935156

Description: 10AX 2 Way Pull Cord Switch With Grey Cord & Bangles



General Information

Dimensions (mm)	70 (Dia) x 42 (D)	
Style	Rounded Profile	
Colour	Polar White	
Insert Colour	Anthracite Grey	
Materials	Cover & Pattress: Urea	Terminal Housing: Urea
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel
	Pull Bell: Urea	
Anti Microbial Certified	Yes	
Operating Voltage (AC)	250	Frequency (Hz) 50
Inductive Load Rating (AX)	10	
Load Rating Comments	Suitable for Fluorescent or Inductive Loads	
Termination Type	Screw	
Terminal Size (mm)	Ø4	Terminal Torque Value (Nm) 0.4
Terminal Capacity - Solid (mm ²)	2 x 1.5 or 1 x 2.5	
2 Way Switch	Yes	
Twin Earth Terminals	No	
Supplied Back Box Depth (mm)	Pattress Supplied	
Back Box Knockouts - Total (mm)	2 x 18 x 6.5 and 2 x 18 x 8	
Back Box Knockouts - Top (mm)	Back Box Knockouts - Sides (mm)	2 x 18 x 6.5
Back Box Knockouts - Bottom (mm)	Back Box Knockouts - Rear (mm)	2 x 18 x 8
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
 All white & grey moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.
 All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.



Catalogue



Range



DoC



Installation

