

Product Code: PRW164

Technical Specification







Description: 4 Gang 2 Way 100W Dimmer Switch



General Information

Plate Dimensions (mm) $146 \text{ (W)} \times 86 \text{ (H)} \times 11 \text{ (D)}$

Plate Fixing Centres - Horizontal (mm) 120.6

Style Square Edge

Materials Front Plate: Urea

Front Plate: Urea Rear Housing: Nylon
Terminals: Brass Terminal Screws: Steel & Yellow Passivated

PCB: Mixed Components

Anti Microbial Certified Yes

Operating Voltage (AC) 250 Frequency (Hz) 50

Load Rating (W) 5 - 100

Load Rating Comments Suitable For LED

Termination Type Screw

Terminal Size (mm) Ø3.5 Terminal Torque Value (Nm) 0.25

Terminal Capacity - Solid (mm²) 2 x 1.5

2 Way Switch Yes

Switch Control Type Press - ON/OFF, Rotate - Dim

Dimmer Technology Type Trailing Edge
Minimum Brightness Programming Available

Minimum Back Box Depth (mm) 25

Ingress Protection IP20
Operational Temperature (°C) -5 to +40

Warranty (Years) 25 Warranty - Electronics (Years) 2

Standards BS EN 60669-1, BS EN 60669-2-1, BS EN 55015, BS EN 61000-3-2

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

We recommend the use of branded LED lamps with all Polar™ trailing edge dimmers. The use of inferior, non-branded lamps may require the nominal rating of the dimmer to be reduced. For further information please contact Click® Technical support team.

Ensure that the main's supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae

Compatible Dimmer Modules

MD9014: 100W Dual Mode LED Dimmer Module

MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module

MD9010: 1-10V Analogue Rotary Dimmer Module

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

Specification is subject to change without notice. Errors & Omissions excluded.









