

REKOR IP

Technical Specification



Product Code: RC228BW

Description: Rekor IP 24/7 IP PoE 2MP 2.8mm Bullet White



General Information

Dimensions (mm)	73(H) x 74(W) x 191(D)
Finish	Powder Coated
Colour	White
Materials	Metal & Plastic
Weight (Kg)	0.32
Warranty (Years)	2

Supply & Power

Operating Voltage (V DC)	12
Power Consumption (W)	8
Power Consumption (A)	0.66
Other Power Sources	PoE (IEEE802.3af)

Media Information

Colour Minimum Illumination (Lux)	0.003 (F1.6, AGS on) 0 Lux (dual light on)
Effective Pixels	1920 x 1080
Sensor Size (")	1/2.8"
Lens size (mm)	2.8
Lens Type	Fixed
Viewing Angle (°)	106(H), 57(V), 115(D)
Electronic Shutter Type	Auto / Manual
Speed (sec/°)	1 to 1/100000
Frames Per Second (FPS)	Main Stream: 1080p (1920*1080), Max 30fps, 720p (1280*720), Max 30fps
Maximum IR Distance (m)	30
IR Wavelength (nm)	850
Microphone Supported	Yes (Built-in)
Speaker Supported	Yes (Built-in)
White Light Range (m)	30
Day/Night	Dual Light (IR & White Light)
Hardware Reset Button	No
Basic Detection	Cross line, intrusion (based on human body detection), motion detection, tampering alarm, audio detection

Network

Interface	1 RJ45; 10/100M Base-TX Ethernet 1 x DC female (2.1x5.5mm)
ONVIF Compliant	Yes; Profile S, Profile G, Profile T
Network Functions	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, SNMP

Supplied 1 x Quick Start Guide, 1 x Camera, 1 x Installation pack, 1 x Mounting sticker

Accessories

BBW1: HDview IP 24/7 4MP & 8MP Bullet Deep Base White

Technical Specification



Product Code: RC228BW

Description: Rekor IP 24/7 IP PoE 2MP 2.8mm Bullet White



General Information

Dimensions (mm)	73(H) x 74(W) x 191(D)
Finish	Powder Coated
Colour	White
Materials	Metal & Plastic
Weight (Kg)	0.32
Warranty (Years)	2

Supply & Power

Operating Voltage (V DC)	12
Power Consumption (W)	8
Power Consumption (A)	0.66
Other Power Sources	PoE (IEEE802.3af)

Media Information

Colour Minimum Illumination (Lux)	0.003 (F1.6, AGS on) 0 Lux (dual light on)
Effective Pixels	1920 x 1080
Sensor Size (")	1/2.8"
Lens size (mm)	2.8
Lens Type	Fixed
Viewing Angle (°)	106(H), 57(V), 115(D)
Electronic Shutter Type	Auto / Manual
Speed (sec/°)	1 to 1/100000
Frames Per Second (FPS)	Main Stream: 1080p (1920*1080), Max 30fps, 720p (1280*720), Max 30fps
Maximum IR Distance (m)	30
IR Wavelength (nm)	850
Microphone Supported	Yes (Built-in)
Speaker Supported	Yes (Built-in)
White Light Range (m)	30
Day/Night	Dual Light (IR & White Light)
Hardware Reset Button	No
Basic Detection	Cross line, intrusion (based on human body detection), motion detection, tampering alarm, audio detection

Network

Interface	1 RJ45; 10/100M Base-TX Ethernet 1 x DC female (2.1x5.5mm)
ONVIF Compliant	Yes; Profile S, Profile G, Profile T
Network Functions	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, SNMP

Supplied 1 x Quick Start Guide, 1 x Camera, 1 x Installation pack, 1 x Mounting sticker

Accessories

BBW1: HDview IP 24/7 4MP & 8MP Bullet Deep Base White

Recording

Storage Type	MicroSD, up to 512GB
--------------	----------------------

Environment

Ingress Protection	IP67
Operating Temperature (°C)	-30 to +60

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuk.com | **W:** espuk.com



CLICK OR SCAN

Catalogue



DoC



Quick Start



CLICK OR SCAN