

REKOR IP

Product Code: RC24KBB

Description: Rekor IP 24/7 IP PoE 2MP 4CH 4 Camera Bullet Kit Black 1TB

Technical Specification Bullet Camera Kit



Component 1		Quantity	Component 2		Quantity	
4 Channel HD 1TB Network Video Recorder (NVR)			1		RC228BB - Rekor IP 24/7 IP PoE 2MP 2.8mm Bullet Black	4
General Information			General Information			
Dimensions (mm)		205 x 205 x 46	Dimensions (mm)		73(H) x 74(W) x 191(D)	
Weight (Kg)		0.6	Finish		Powder Coated	
Supply & Power			Colour			Black
Operating Voltage (V DC)		48	Sensor Size (")		1/2.8" Progressive CMOS	
Power Consumption (mA)		<9W	Lens size (mm)		2.8	
Media Information			Effective Pixels		2MP (1920 x 1080)	
Display Video Output		1 x HDMI, 1 x VGA	Maximum IR Distance (m)		30	
Display Split		1 & 4	White Light Range (m)		30	
Display Resolutions		HDMI: 3840x2160/30Hz, 1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz VGA: 1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	Day/Night		Dual Light (IR & White Light)	
Sync Playback		4 Channel	Basic Detection		Cross line, intrusion (based on human body detection), motion detection, tampering alarm, audio detection	
Backup Mode		USB2.0 devices	Operating Voltage (V DC)		12	
Recording			Power Consumption (W)		8	
Internal HDD		1TB (1 x SATA)	Other Power Sources		PoE (IEEE802.3af)	
Recording Bandwidth (Mbps)		64	Lens Type		Fixed	
Video/Audio Compression		H.265/H.264	Viewing Angle (°)		106(H) x 57(V) x 115(D)	
Recording Resolution		4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	Frames Per Second (FPS)		Main Stream: 1080p (1920*1080), Max 30fps, 720p (1280*720), Max 30fps	
Network			Speaker Supported		Yes (built-in)	
Network Connection		1 RJ45 10M/100M self-adaptive Ethernet Interface	Microphone Supported		Yes (built-in)	
Network Functions		TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SMTP, RTSP	Reset Key		No	
PoE Channels		4 RJ45 10M/100M self-adaptive Ethernet Interface	ONVIF Compliant		Yes; Profile S, Profile G, Profile T	
USB Interface		2 x USB2.0	Network Functions		IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, SNMP	
Inputs & Outputs			Ingress Protection		IP67	
Video Input Channels		4	Operating Temperature (°C)		-30 to +60	
Audio Output Channels (RCA)		1	Weight (Kg)		0.32	
Environment						
Operating Temperature (°C)		-10 to +55				
Relative Humidity Resistance (%)		≤ 90 RH (non-condensing)				

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | F: +44 (0)1527 515143
E: info@espuk.com | W: espuk.com



CLICK OR SCAN

Catalogue



DoC



Installation



Quick Start



CLICK OR SCAN

CATEGORY 2



Component 3

18.3M IP Cables

Quantity

4

Component 4

24/7 NVR Power Supply Unit

Quantity

1

General Information

Colour	Black
Length (M)	18.3
Category	Cat-5e, UTP
Pre-wired	Yes
Terminated Connections	2 x RJ45

General Information


Supply Voltage (V AC)	110 - 240
Output Rating	48VDC

Warranty Years 2

Supplied 4 Channel NVR
PSU for NVR
4 x RC228BB Bullet Cameras
Kit Cable for Each Camera

Accessories

IPIN1POE: 1 Channel POE Injector (30W)
S4POE: 4 Port PoE Switch 60W
CABIP10 : 10 Metre CAT-5e External Use Data Cable
CABIP20: 20 Metre CAT-5e External Use Data Cable
CABIP40: 40 Metre CAT-5e External Use Data Cable
CABIP80: 80 Metre CAT-5e External Use Data Cable
BBB1: HDview IP & Rekor IP 24/7 Bullet Deep Base - Black



CLICK OR SCAN

Catalogue

CLICK OR SCAN

Catalogue

CLICK OR SCAN

Catalogue

CLICK OR SCAN

Installation