

Technical Specification

Product Code: VPAB053BK

Luckinslive 389108377



Description: 13A Fused Connection Unit With Neon & Optional Flex Outlet



General Information



Plate Dimensions (mm) Dimensions With Gasket (mm) Plate Fixing Centres - Horizontal (mm) Style Finish Insert Colour Gasket Colour	91 (W) x 91 (H) x 9 (D) 60.3 Victorian Antique Brass Black		
Materials	Black Front Plate: Stainless Steel Neon Lens: Polycarbonate Terminal Screws: Steel & Yellow Passivated Earth Strap: Mild Steel	Insert, Fuse Drawer & Terminals: Brass I Internal Busbars: For Gasket: Nylon	Ŭ
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Fuse Fitted Type	Plug Top Cartridge Fuse		
Termination Type	Screw		
Terminal Size (mm)	Ø5 Term	inal Torque Value (Nm)	2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4		
Switched	No		
Twin Earth Terminals	Yes		
Neon Indicator	Yes	Indicator Colour	Red
Product Marking	Fused		
Flex Outlet Available	Yes		
Flex Outlet Location	Front of Plate Flex (Outlet Dimension (mm)	Ø10
Minimum Back Box Depth (mm)	25		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		
Standards BS 1363-4, BS 1362			

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com









UK Design Registration: 3015621

