

**Product Code:** VPBN571UBK

**Description:** 13A Ingot 1 Gang Switched Socket Outlet With Single 2.1A USB Outlet



## General Information

<b>Plate Dimensions</b>	88mm (W) x 88mm (H) x 8mm (D)	
<b>Dimensions With Gasket</b>	91mm (W) x 91mm (H) x 9mm (D)	
<b>Plate Design &amp; Finish</b>	Victorian Black Nickel	
<b>Insert &amp; Gasket Colour</b>	Black	
<b>Materials</b>	Front Plate: Stainless Steel	Insert: Urea
	Housing: Nylon	Switch Cover: Stainless Steel
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass
	PCB: Mixed Components	Earth Strap: Mild Steel
<b>Maximum Voltage</b>	250V~ 50Hz	
<b>Load Rating</b>	13A	
<b>Plate Fixing Centres</b>	60.3mm	
<b>Terminal Size</b>	5mmø	
<b>Terminal Torque</b>	1.2Nm	
<b>Terminal Capacity</b>	3 x 2.5mm <sup>2</sup> or 2 x 4mm <sup>2</sup>	
<b>Single Pole</b>	Yes	
<b>Twin Earth Terminals</b>	Yes	
<b>USB Charging Output Total</b>	5V DC, 2.1A	
<b>Number Of USB Outputs</b>	1	
<b>USB Type</b>	USB Type "A"	
<b>USB Standby Current</b>	2mA	
<b>Product Markings</b>	USB 5V 2.1A	
<b>Ingress Protection</b>	IP20	
<b>Back Box Depth</b>	25mm Minimum	
<b>Termination Type</b>	Screw	
<b>Operational Temperature</b>	-5°C to +40°C	
<b>Warranty</b>	10 Years, 1 Year Electronics	
<b>Standards</b>	BS 1363-2: 2016 +A1: 2018 BS EN 62368-1: 2014, BS EN 62680-1-1: 2015	

## Additional Information

The USB circuits within this socket outlet are designed to withstand insulation resistance tests at 500V. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.