

## **Technical Specification**

CLICK® ScolmoreGROUP

Product Code: VPBZ039BK

Description: 2A Round Pin Socket Outlet





Insert: Urea

Terminals: Brass

Gasket: Nylon

Terminal Torque Value (Nm)

Internal Busbars: Formed Pressed Brass

## **General Information**

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm)  $91 \text{ (W)} \times 91 \text{ (H)} \times 9 \text{ (D)}$ 

Plate Fixing Centres - Horizontal (mm) 60.3

Style Victorian
Finish Matt Bronze

Insert Colour Black Gasket Colour Black

Materials Front Plate: Stainless Steel

Rear Housing: Nylon

Terminal Screws: Steel & Yellow Passivated

Earth Strap: Mild Steel

Frequency (Hz) 50

Operating Voltage (AC) 250
Resistive Load Rating (A) 2
Termination Type Screw

Terminal Size (mm) Ø5

Terminal Capacity - Solid (mm<sup>2</sup>)  $3 \times 1.5$ 

Anti Microbial Certified

Switched No

Twin Earth Terminals No

Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Standards BS 546

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.









