

# **Technical Specification**

Product Code: VPBZ422

Description: 10AX 2 Gang 2 Way Toggle Plate Switch





### **General Information**

Dimensions (mm) 91 (W) x 91 (H) x 40 (D) Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm)

Style Victorian Finish Matt Bronze

Gasket Colour Black Switch Finish Matt Bronze

Materials Front Plate: Stainless Steel

Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Operating Voltage (AC) 250

Inductive Load Rating (AX)

Anti Microbial Certified

Load Rating Comments Suitable for Fluorescent or Inductive Loads

Termination Type Screw

Terminal Size (mm) 4.9 x 4.1

Terminal Capacity - Solid (mm²) 4 x 1.5 or 2 x 2.5

Modular Rocker Switches Yes

2 Way Switch Yes

Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40 Warranty (Years) 20

Standards BS EN 60669-1

# Frequency (Hz)

Terminals: Brass

Earth Strap: Mild Steel

Terminal Torque Value (Nm)

Switch Front & Nut: Cast Zinc

Contacts: Silver "on-lay" Copper / Brass

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Intermediate toggle switches modules are available which interchange with the modules fitted. Order MDg125BZ for Matt Bronze finish.

E: sales@scolmore.com | W: scolmore.com









