

Product Code: VPBZ522BK
 Description: 20A Ingot Double Pole Plate Switch With Optional Flex Outlet



General Information

Dimensions (mm)	g1 (W) x g1 (H) x 26 (D)		
Plate Dimensions (mm)	88 (W) x 88 (H) x 8 (D)		
Dimensions With Gasket (mm)	g1 (W) x g1 (H) x g (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Victorian		
Finish	Matt Bronze		
Insert Colour	Black		
Gasket Colour	Black		
Materials	Front Plate: Stainless Steel Switch Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Gasket: Nylon		
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	20	Terminal Torque Value (Nm)	1.8
Termination Type	Screw	Flex Outlet Dimension (mm)	
Terminal Size (mm)	Ø5		
Terminal Capacity - Solid (mm²)	3 x 2.5	Flex Outlet Dimension (mm)	
Double Pole Switch	Yes		
Twin Earth Terminals	Yes	Flex Outlet Dimension (mm)	
Flex Outlet Available	Yes		
Flex Outlet Location	Front of Plate	Flex Outlet Dimension (mm)	
Minimum Back Box Depth (mm)	25		
Ingress Protection	IP20	Flex Outlet Dimension (mm)	
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20	Flex Outlet Dimension (mm)	

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

