

## **Technical Specification**

CLICK® ScolmoreGROUP

Product Code: VPBZ553BK

Description: 13A Ingot Fused Connection Unit With Neon & Optional Flex Outlet





Insert & Housing: Urea

Earth Strap: Mild Steel

Frequency (Hz)

Indicator Colour

Flex Outlet Dimension (mm) Ø10

Neon Lens: Polycarbonate

Terminal Screws: Steel & Yellow Passivated

Red

## **General Information**

 $\begin{array}{ccc} \textbf{Dimensions (mm)} & 91 \,(\text{W}) \times 91 \,(\text{H}) \times 25 \,(\text{D}) \\ \textbf{Plate Dimensions (mm)} & 88 \,(\text{W}) \times 88 \,(\text{H}) \times 8 \,(\text{D}) \\ \textbf{Dimensions With Gasket (mm)} & 91 \,(\text{W}) \times 91 \,(\text{H}) \times 9 \,(\text{D}) \\ \end{array}$ 

Plate Fixing Centres - Horizontal (mm) 60.3

Style Victorian
Finish Matt Bronze
Insert Colour Black
Gasket Colour Black

Materials Front Plate: Stainless Steel

Fuse Drawer Cover: Stainless Steel

Terminals: Brass

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Anti Microbial Certified No
Operating Voltage (AC) 250

Resistive Load Rating (A) 13

Fuse Fitted Type Plug Top Cartridge Fuse

Termination Type Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Switched No Twin Earth Terminals Yes

Neon Indicator Yes

Product Marking Fused Flex Outlet Available Yes

Flex Outlet Location Front of Plate

Minimum Back Box Depth (mm) 25

Ingress Protection IP20
Operational Temperature (°C) -5 to +40

Warranty (Years) 20

**Standards** BS 1363-4, BS 1362

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installating

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com









