

Product Code: VPBZ66o
 Description: 20A Double Pole 1 Gang Plate Key Lockable Switch



General Information

Dimensions (mm)	91 (W) x 91 (H) x 36 (D)	
Plate Dimensions (mm)	88 (W) x 88 (H) x 8 (D)	
Dimensions With Gasket (mm)	91 (W) x 91 (H) x 9 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Victorian	
Finish	Matt Bronze	
Gasket Colour	Black	
Materials	Front Plate: Stainless Steel	Insert: Urea
	Earth Plate & Yoke: Mild Steel	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	GridPro Module: GM2018PW
Anti Microbial Certified	No	
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	20	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Modular Rocker Switches	Yes	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Product Marking	On & Off	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Two keys provided (Spare keys available: SP66o)
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

