

## **Technical Specification**

Product Code: VPBZ750BK

Description: 13A Ingot Fused Connection Unit





## **General Information**

Dimensions (mm) 91 (W) x 91 (H) x 25 (D) Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm)

Style Finish Matt Bronze

Insert Colour Black Gasket Colour Black

Materials Front Plate: Stainless Steel

Fuse Drawer Cover: Stainless Steel

Terminal Screws: Steel & Yellow Passivated

Earth Strap: Mild Steel

Insert & Housing: Urea Terminals: Brass

Frequency (Hz)

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Anti Microbial Certified

Operating Voltage (AC) 250

Resistive Load Rating (A)

Fuse Fitted Type Plug Top Cartridge Fuse

Termination Type Screw

Terminal Size (mm) Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Switched No

Twin Earth Terminals Yes Product Marking Fused

Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

**Standards** BS 1363-4, BS 1362

Terminal Torque Value (Nm)

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal











Specification is subject to change without notice. Errors & Omissions excluded.