

Product Code: VPCH751BK

Technical Specification



Description: 13A Ingot Double Pole Switched Fused Connection Unit









Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

General Information

Dimensions (mm) 91 (W) x 91 (H) x 26 (D)

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm)

Style

Finish Polished Chrome

Insert Colour Black Gasket Colour

Materials Front Plate: Stainless Steel

Insert & Housing: Urea Switch & Fuse Drawer Cover: Stainless Steel Terminals: Brass

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Anti Microbial Certified Operating Voltage (AC) 250 Frequency (Hz)

Resistive Load Rating (A)

Fuse Fitted Type Plug Top Cartridge Fuse

Termination Type Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm)

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Switched Yes Double Pole Switch Yes

Twin Earth Terminals Yes Product Marking Fused

Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362

Specification is subject to change without notice. Errors & Omissions excluded.

E: sales@scolmore.com | W: scolmore.com









