


Product Code: VPSC536WH

Technical Specification



Description: 13A Ingot 2 Gang Double Pole Switched Socket Outlet







Insert & Housing: Urea

Earth Strap: Mild Steel

Frequency (Hz) 50

Contacts: Silver "on-lay" Copper / Brass

Terminals: Brass

Terminal Torque Value (Nm) 2

General Information

Plate Dimensions (mm) 146 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 149 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

> Style Victorian

Finish Satin Chrome

Insert Colour White Gasket Colour White

> Materials Front Plate: Stainless Steel

> > Switch Cover: Stainless Steel

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Anti Microbial Certified

Operating Voltage (AC) 250

Resistive Load Rating (A) 13

> **Termination Type** Screw

Terminal Size (mm)

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Double Pole Switch

Twin Earth Terminals

Minimum Back Box Depth (mm) Ingress Protection

Operational Temperature (°C) -5 to +40

> Warranty (Years) 20

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal








UK Design Registration: 3015621





Specification is subject to change without notice. Errors & Omissions excluded.