


Product Code: VPSC751BK

Technical Specification



Description: 13A Ingot Double Pole Switched Fused Connection Unit







Insert & Housing: Urea

Earth Strap: Mild Steel

Frequency (Hz) 50

Contacts: Silver "on-lay" Copper / Brass

Terminals: Brass

Terminal Torque Value (Nm) 2

General Information

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Victorian

Finish Satin Chrome

Insert Colour Black Gasket Colour Black

> Materials Front Plate: Stainless Steel

> > Switch & Fuse Drawer Cover: Stainless Steel

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Anti Microbial Certified

Operating Voltage (AC) 250

Resistive Load Rating (A)

Fuse Fitted Type Plug Top Cartridge Fuse

Termination Type Screw Terminal Size (mm)

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

> Switched Yes

Double Pole Switch Twin Earth Terminals Product Marking Fused

Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.







UK Design Registration: 3015621



Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362

E: sales@scolmore.com | W: scolmore.com